

the microphone input port.)

4. Volume Control

① Press the power button on the TX to turn on/off the mute. When mute is on, the red pairing indicator on the TX keeps on.

② Short press the gain adjustment button of the TX to adjust the volume for 4 levels.

③ Short press the gain adjustment of A/B TX buttons on the RX to adjust the volume of A/B TX.

5. Noise Reduction

Short press the noise reduction button on the TX to turn on/off the noise reduction function. When the noise reduction on, the red and blue indicator light on the TX status light up at the same time.

6. Switch the Channel Mode

Short press the power button on the RX to switch the mono/stereo/protected channel mode.

Default mono mode. When switching to stereo mode, the red pairing indicator light keeps on. When switching the protection channel mode, the blue&red pairing indicator lights light on at the same time.

7. Charging

① Connect the charging cable through the Type-C port to charge the charging case, and fully charged about 3.5 hours.

② The TX/RX: Automatically charge through the contact point of the charging case after put into the charging case.

③ Connect the charging cable through the Type-C port of the receiver and the transmitter, and fully charged in about 2 hours.

Specifications	
TX Transmitter	
Wireless Transmission	Digital 2.4GHz
RF Frequency Band	2400-2483.5MHz
Working Distance	656ft/200m (LOS area), 164ft/50m (NLOS area)
Mounting	Pocket Clip
Audio Input	3.5 mm TRS Mic Input
Power Requirements	5V 1A
Battery Type	Built-in Lithium Battery, 400mAh
Battery Charging Time	2H
Battery Life	8H
Dimensions	52*42*16mm
Material	ABS
Weight	35g

RX Receiver	
Wireless Transmission	Digital 2.4GHz
RF Frequency Band	2400-2483.5MHz
Working Distance	656ft/200m (LOS area), 164ft/50m (NLOS area)
Latency	20ms
Mounting	Pocket Clip
Number of Audio Channels	2
Audio Output	3.5 mm TRS Mic Output 3.5 mm TRS Headphone Output Type-C Output
Gain	1~30dB

Power Requirements	5V 1A
Battery Type	Built-in Lithium Battery, 400mAh
Battery Charging Time	2H
Battery Life	8H
Dimensions	52*42*16mm
Material	ABS
Weight	35g

Microphone

Form Factor	Built-in/External Mic
Polar Pattern	Omnidirectional
Frequency Range	50Hz-20KHz
Sensitivity	-40dB (± 3 dB, re 1V/Pa at 1KHz)
Maximum SPL	120dB SPL (at 1KHz)

Charging Case

Battery Type	3400mAh
Battery Charging Time	3.5H
Charging Port	Type-C
Power Requirement	5V 1A
Dimension	176*80*53mm
Weight	227g

Warranty

Warranty Period

Thank you for purchasing SYNCO products.

1. Customers are entitled to free replacement or repair service in case of quality defect(s) found in the product under normal use within 30 days upon receipt of the product.

2. Original SYNCO products are entitled to **12-month** limited warranty service. The warranty period begins on the date of purchase of brand new, unused products by the first end-user.

Within the warranty period, if product defect or failure is attributable to material deflection or technological problem, the defective product or defective part will be repaired or replaced without charge (service and materials fee).

Warranty Exclusions and Limitations

- Faults resulted from inappropriate use of a product without following its operation specification
- Artificial damage, e.g. crash, squeeze, scratch, or soaking
- Modifications to a product by its user or a third party without prior written consent of SYNCO, e.g. replacement of element or circuit, label alteration
- The code on product is inconsistent with that of warranty certificate, or the code on the product or warranty certificate is altered or torn off
- All consumable accessory attached to a product, like cable, wind muff, battery
- Faults as a result of force majeure, such as fire, flood, lightning, etc.

Warranty Claim Procedure

- If failure or any problem occurs to your product after purchase, please contact a local agent for assistance, or you can always contact SYNCO's customer service through email at support@syncoaudio.com.
- Please retain your sales receipt and warranty certificate as proof of purchase. If any of these documents is missing, only sales return or chargeable service will be provided.
- If the SYNCO product is out of the warranty coverage, the service and the parts cost will be charged.

WARRANTY CERTIFICATE	
Please register your warranty. Meanwhile, you are welcomed to contact us via Email: support@syncoaudio.com	
USER INFORMATION	Customer Name:
	Phone Number:
	Email:
SALES INFORMATION	Address:
	Sales Date:
	Model:
REPAIR RECORD	Product Code:
	Dealer:
	Service Date:
Technician:	
Issue:	

RESULT Solved Unsolved Returned(Replaced)

Guangzhou Zhiying Technology Co., Ltd

📍 Room 2401, 24 / F, South Tower, Lisheng Plaza, No. 68 Huadi Avenue, Liwan District, Guangzhou, China, 510000

✉ support@syncoaudio.com

🌐 www.syncoaudio.com

🌐 <https://www.facebook.com/syncomicrophones>