




Zoom Reflector

A classic among our Light Shaping Tools

The classic Zoom Reflector has served photographers all over the world for more than four decades. The new version retains all of the attractive features of the original but adds an integrated grid holder and even smoother and more precise light characteristics. The result is one of the most versatile reflectors available, capable of providing the light of a normal reflector, a wide-angle reflector and everything in between. Standard reflector for Pro Head Plus and Acute/D4 Heads.



Lighting Diagram



- A. Set
- B. Zoom Reflector on background
- C. Zoom Reflector slightly above model's face level

Aperture: f/8.0
Shutter speed: 1/125
ISO: 100

Light Spread



Zoom Reflector at zoom position 5



Zoom Reflector at zoom position 7



Zoom Reflector at zoom position 7 with 10° Grid



Zoom Reflector at zoom position 9

ZOOM REFLECTOR

Specifications

Light Spread:	45–100°
Output at 2m with 2400 Ws @ ISO 100:	f/45.1 at zoom position 7
Compatible heads:	All Profoto heads

Measurements

Diameter	19.3 cm, 7.6 in
Size	18 cm depth, 5.9 in depth
Weight	0.3 kg, 0.66 lb

Product number

Zoom Reflector	100785
----------------	--------

Light Characteristics

Profoto reflectors are zoomable. The graphics below show the reflector's light characteristics depending on zoom position.

BEAM ANGLE	105°	75°	35°
POSITION	10	7	6

For more information on Profoto Zoom System please visit www.profoto.com/zoom

Associated accessories

Barndoors	100671
Grid 20°	100606
Grid 10°	100605
Grid 5°	100646
Grid Kit 5°, 10° & 20°	900849
Zoom-Cap	100786
Grid & Filterholder	900649
Grid/Grid & Filterholder Kit	900362
Mounted on Grid & Filterholder:	
Snoot	100651

Popular applications

- Portrait
- Special effects

Profoto[®]
The Light Shaping Company™